

CUPID
WALL HANGING OR TABLE RUNNER
© C.A. COLUCCI 2008

WALL HANGING: A quick easy project you can finish in less than one day.

MATERIALS

FABRIC FOR BACKING:

CUT ONE, 21-inch wide x 19 1/2-inch high

BATTING: (I like the fusible batting)

CUT ONE, 21-inch x 19 1/2-inch

CUT TWO, 3 1/2-inch x 6 1/2-inch, *for hanging tabs*

FABRIC FOR BACKGROUND:

CUT ONE, 21-inch wide by 19 1/2-inch high

2 STRIPS, 2 1/4-inch by width of fabric, *for binding*

CUT FOUR, 3 1/2-inch x 6 1/2-inch, *for hanging tabs*

CUPID:

FABRIC FOR CUPID (I used a very light pink)

1 fat quarter (18 x 22-inches)

FABRIC FOR HAIR (I used a marbled gold)

1 - 6 1/2-inch square

FABRIC FOR WINGS (I used a white-on-white print)

1 - 4 1/2-inch square

FABRIC FOR HEART (I used a medium pink print)

1 - 6-inch square

FABRIC FOR EYES (I used a light blue background with dark blue pupils)

1 - light colored scrap

1 - dark colored scrap

FUSIBLE WEBBING



Read all instructions before you begin. Yardage is based on a 42/44-inch width of fabric.

Because images downloaded from the Internet may distort during the printing process, we recommend verifying all pattern pieces and templates before cutting the fabrics for your project. Make any adjustments, as needed, to ensure a successful outcome.

I like to have everything ready before I begin. That way I can sew until it is done.

1. I recommend taping together the full pattern, as a guide for placement and markings.
2. Cut backing, batting, and background fabrics, including the tabs and the binding.
3. Trace, do not forget to use the reverse pattern (fusible web pattern A or B) when using fusible webbing. (Pattern A faces left, and pattern B faces right) I like to cut out the center of the fusible webbing on the larger pieces to make it less stiff because of layering.
4. Iron the fusible webbing to the wrong side of the fabrics. Then cut out the pattern piece. Once the pattern pieces are cut out, this is the best time to trace all the marking lines onto the fabric. (Use the full pattern and your favorite way of tracing.)
5. Mark the center of your background fabric by folding lengthwise and finger pressing, then widthwise and finger pressing. Using the full pattern as a guide, arrange your pattern pieces on the background and press in place. (I find it best to lay all of the pieces on the background before the final pressing.)
6. Layer the backing, (wrong side facing up) lay the batting on top of the wrong side of fabric. Then, lay the background, right side up, on top of the batting. Press all three layers together. (I like the fusible batting.) If you are not using the fusible batting, pin the four corners and a pin in the center of each side. This just helps keep all layers in place.
7. Buttonhole stitch each fused piece, through all layers. This also serves as a portion of the quilting. (Make sure you use a darker color for Cupid to highlight his face, arms, and legs, etc... I used a darker color of pink.)

8. I used a narrow satin stitch for all of the markings, including the words. (If you prefer, you can embroider the markings and the words.)
9. Make the tabs. Layer fabric, rights sides together, then put the batting on the bottom for sewing. Sew 1/4-inch **seams on three sides**. Turn right side out and press.
10. Prepare the binding and set aside.
11. Quilt the open areas around Cupid. Press.
12. Trim the wall hanging to measure 19 1/2-inches wide by 18-inches high.
13. Pin tabs to backing, 1-inch from side and raw edges even with the top. Because I machine sew my binding, I sew the binding to the back of the wall hanging first. Then iron the binding, folding it to the right side of the fabric and the tabs ironed straight up. (When stitching the binding down, on the front side of the wall hanging, make sure the tabs are loose and up away from the top.)
14. Fold the tabs, 2 inches from the top, and stitch over the top of the binding.
15. I chose to sew a button on the tab, strictly for decoration.

CUPID TABLE RUNNER

FABRIC FOR BACKING: 5/8-yard

CUT ONE, 19 1/2-inch by width of fabric

BATTING: 5/8-yard

CUT ONE, 19 1/2-inch by width of fabric

FABRIC FOR BACKGROUND AND BINDING: 3/4-yard

CUT ONE, 19 1/2-inch by width of fabric

3 STRIPS, 2 1/4-inch by width of fabric, *for binding*

DOUBLE ALL FABRICS USED FOR CUPID (You will be making two Cupids)

USE BOTH FULL PATTERNS (A and B)

USE BOTH FUSIBLE PATTERNS (A and B)

FOLLOW DIRECTIONS

1 - # 4, EXCLUDING THE TABS.

5, Center the full pattern from the top to the bottom, and measure 3 1/2-inches from the sides to the edge of lowest foot. (Cupids should face the center)

6 - # 8

Skip # 9

10, # 11

12, Trim to 18-inches high. Square off sides and cut approximately 1-inch off.

13, For binding only.

© C. A. Colucci 2008

erikhomemade.typepad.com; *used with permission*